

On-grid Three Phase Inverter

Suntrio Plus 25K/33K/40K/50K/60K



BENEFITS

Flexible and Efficient

- Optimized global MPPT algorithm, MPPT efficiency higher than 99.5%
- Three MPPT which are compatible to all kinds of solar roofs
- Max. efficiency of 98.8%, European efficiency of 98.5%
- Super wide input voltage range(180V-1000V), supporting various solar panels and string designs

Convenient Installation

- Aluminum case design, smaller and lighter
- Integrate DC combiner box, reduce system cost
- Separate area for maintenance, easy and quick for repair

Smart and Easy to Use

- One-button safety setting, easy configuration of all parameters
- Built-in independent RTC chip, supporting data storage of 25 years
- Integrated LCD graphical display, showing daily/monthly/yearly generation
- Integrated with the function of reactive power control & ZVRT, responds to power grid dispatching, energy management of grid
- Integrate string current monitoring, monitor string working status

Safe and Reliable

- IP65 protection for indoor and outdoor installation
- Optional DC&AC surge protection, guarantee system safety
- Optional Anti-PID module, protect panels from PID damage
- Aluminum case design to enhance heat dissipation and resist rust corrosion, prolong life time

Technical Data

Suntrio Plus 25K/33K/40K/50K/60K

Type	Suntrio Plus 25K	Suntrio Plus 33K	Suntrio Plus 40K	Suntrio Plus 50K	Suntrio Plus 60K
Input (DC)					
Max. DC Power [W]	30300	36300	48400	60500	72000
Max. DC Voltage [V]			1000		
MPPT Voltage Range [V]		180-900		280-900	
Nominal DC Voltage [V]			600		
Start Voltage[V]		200		300	
Min. DC Voltage[V]		180		250	
Max. DC Input Current PV1 / PV2 [A]	22/22/22		40/30/30		40/40/40
Number of MPPT		3			
Number of DC Connection Sets per MPPT	2/2/2		4/3/3		4/4/4
DC Switch			Integrated		
Output (AC)					
Rated AC Power [W](@230V,50Hz)	25000	30000	40000	50000	60000
Max. AC Power [W]	27500	33000	44000	55000	60000
Rated AC Current [A]	37.9	45.5	61.0	76.0	87.0
Max. AC Current [A]	42.0	50.0	65.0	80.0	90.0
Nominal AC voltage/ range		3/N/PE, 220/380V, 230/400V, 240/415V; 180V-280V/312V-485V			
Grid frequency / range		50Hz, 60Hz / 44Hz-55Hz, 54-65Hz			
Power factor,adjustable [$\cos \varphi$]		0.8 leading~0.8 lagging			
Total Harmonic Distortion (THDi)		< 3% (at nominal power)			
Feed-in			3L+N+PE		
Efficiency					
Max. Efficiency	98.6%	98.8%	98.8%	98.8%	98.9%
Euro Efficiency (@ 600Vdc)	98.4%	98.5%	98.5%	98.5%	98.6%
MPPT Accuracy			>99.5%		
Protection					
Internal Over-voltage Protection			Integrated		
DC Insulation Monitoring			Integrated		
DCI Monitoring			Integrated		
GFCI Monitoring			Integrated		
Grid Monitoring			Integrated		
AC Short Circuit Current Protection			Integrated		
LVRT			Integrated		
Thermal Protection			Integrated		
AC Surge Protection			Integrated (II)		
String Current Monitoring			Integrated		
Anti-PID Module			Optional		
DC Surge Protection			Integrated (II)		
DC Fuse			Optional		
Anti-island protection monitoring			AFD		
Interface					
DC Connection			MC4/H4		
AC Connection			Terminal Block		
LCD & LED Display			3.5 inch Graphic LCD Display		
Display Language			English		
Communication port			2*RS485, 1*RS232		
Communication			Wi-Fi/GPRS/Ethernet (Optional)		
General Data					
Topology			Transformerless		
Consumption at Night [W]			<0.6		
Consumption at Standby [W]			<10		
Operating Temperature Range			-25°C to +60°C (45°C to 60°C with derating)		
Cooling Method			Intelligent fan		
Ambient Humidity			0% to 100% Non-condensing		
Altitude			3000m (> 2000m power derating)		
Noise [dBA]			<35		
Ingress Protection			IP65 (Indoor & Outdoor Installation)		
Mounting			Rear Panel		
Dimensions (H*W*D) [mm]	700*530*260		800*550*280		
Weight [kg]	48		68		
Standard Warranty [Year]		5 (Standard) / 10 / 15 / 20 / 25 (Optional)			
Certificates		IEC62109-1/2, IEC61000-6-2/3, IEC61683, IEC60068-2, IEC62116, IEC61727, PEA/MEA, NRS 097-2-1, UTE-C-15-712-1, VDE0126-1-1/A1, VDE-AR-N 4105, AS4777.2, AS4777.3, C-TICK, CQC NB/T 32004, G83-2, G59-3, NBR 16149, NBR 16150, TF 3.2.1			