



# Product data sheet

## Power tools for trade & industry

Drywall Screwdriver

## GSR 6-45 TE



Universal corded drywall screwdriver

### The most important data

Rated input power	701 W
Self-drilling screw diameter	6 mm
Torque, max. (soft screwdriving applications)	12 Nm

**Order number** 0 601 445 140

[> More product information](#)

## Technical data

### Technical data

Rated input power	701 W
Torque, max. (soft screwdriving applications)	12 Nm
Bit holder	1/4" internal hexagon
Power output	327 W
No-load speed	0 – 4.500 rpm
Weight	1.4 kg
Tool dimensions (length)	295 mm
Tool dimensions (height)	207 mm
Rated torque	1.3 Nm
Packaging dimensions (width x length x height)	300 x 350 x 110 mm

### Screwdriving

Self-drilling screw diameter	6 mm
------------------------------	------

## Noise/vibration information

### Screwdriving

Vibration emission value ah	2.5 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

**BOSCH**

Invented for life

# Product data sheet

Power tools for trade & industry

---

## Advantages:

- Optimal all-round performer in a wide range of materials due to a delivered combination of high torque and high speed
- Ergonomic design and depth stop for comfortable and effortless one-handed operations
- Exact shut-off clutch for screwdriving at constant precise depths

**HEAVY  
DUTY**