

# EFI-4 AC 25/0.03



## Specifications

|                            |                                                        |
|----------------------------|--------------------------------------------------------|
| ETI Code                   | 002062142                                              |
| Description                | EFI-4 AC 25/0.03                                       |
| Weight                     | 305                                                    |
| Level                      | Residual current circuit breakers RCCB and accessories |
| Function                   | RCCB                                                   |
| Rated current (A)          | 25                                                     |
| Type                       | AC                                                     |
| Rated residual current (A) | 0,03                                                   |
| Rated voltage (V)          | 400                                                    |
| No. Of poles               | 4                                                      |
| Catalogue Group            | EFI-4 A, AC A and AC type                              |

Online product page

## Other documentation



Technical data catalogue  
3D Model  
Instruction manual  
EU declaration



## ETIM international clasification

|                                                   |          |
|---------------------------------------------------|----------|
| Mounting method                                   | EV004369 |
| Built-in depth                                    | 68mm     |
| Nominal rated current                             | 25 A     |
| Nominal rated voltage                             | 400V     |
| Number of poles                                   | 4        |
| Rated fault current                               | 0,03 A   |
| Leakage current type                              | AC       |
| Selective protection                              |          |
| Short-circuit breaking capacity (Icw)             | 10kA     |
| Surge current capacity                            | kA       |
| Construction size (in accordance with DIN 43880)  |          |
| Width in number of modular spacings               | 4        |
| Short-time delayed tripping                       |          |
| Frequency                                         | 50 Hz    |
| Degree of protection (IP)                         | IP20     |
| Rated short-circuit breaking capacity IEC 60947-2 | kA       |
| Additional equipment possible                     |          |

