Key **Features**

10-point Projected Capacitive Touch | SuperClear® MVA-type panel technology | Frameless Design | Versatile Connectivity | Durable, Scratch-resistant Screen



Product **Description**

Laid flat or angled for customized comfort, this display delivers touchscreen versatility to the max. Offering fantastic flexibility for retail, education, or business settings, the ViewSonic® TD2430 is a 24" (23.6" viewable) Full HD display with 10-point multi-touch functionality. Delivering adjustable positioning, wide-angle viewing, and a durable design, the TD2430 has everything to accommodate your unique needs. Adding even more convenience, cross-compatibility with a wide range of operating systems includes Windows 10, and certain Android and Linux versions.* With a sleek edge-to-edge screen and frameless bezel, this intuitive touchscreen performs like your favorite tablet or smartphone to deliver a highly accurate, ultra-responsive touch experience ideal for interactivity in public environments, kiosk and wayfinding applications, classroom settings, and more. *Supports Windows 7/8/10, Linux 2.6.38 or later, and Android 4.0 or later.



Menu Control Panel VESA Compatible Wall Mount (100 x 100 mm) DC In Headphone Audio In



VGA DisplayPort Internal Speakers HDMI USB 3.0 Type B USB 3.0 Type A (x2)









Display:

Display Size (in.): 24 Viewable Area (in.): 23.6 Resolution: 1920 x 1080 Static Contrast Ratio: 3,000:1 Dynamic Contrast Ratio: 50,000,000:1 Brightness: 250 cd/m2 Backlight Life (Hours): 40,000 Response Time (Typical GTG): 25ms MVA Panel Type: Colors: 16.7M

178° horizontal, 178° vertical Viewing Angles:

Light Source: LED

Panel Surface: 7H Scratch Resistant Surface Hardness

Aspect Ratio: 16:9

Compatibility:

PC Resolution (max): 1920 x 1080

Touch:

Projective Capacitive Touch Technology: Touch Points: 10-Point Touch

Connector:

USB 3.0 Type A(2), USB 3.0 Type B(1), VGA(1), HDMI 1.4(1), Display Port(1)

Audio:

Internal Speakers: 2.5W (x2)

Video Signal:

Frequency Horizontal: Analog: 24 \sim 82Hz, Digital: 15 \sim 82Hz Analog: 50 ~ 75Hz, Digital: 24 ~ 75Hz Frequency Vertical:

Video Input:

Analog Sync: Separate Sync / Composite Sync / Sync on Green, TMDS, PCI-E

Power:

19W Eco Mode (Conserve): Eco Mode (optimized): 22W Consumption (typical): 25W Consumption (max): 28W

Voltage: AC 100-240V (universal), 50-60Hz

Stand-by: 0.5W

Controls:

Physical Controls: 1, 2, Up, Down, Power

Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) On Screen Display:

Operating Conditions:

32-104° F (0 - 40° C) Temperature:

Humidity (non-condensing): 20-90%

Ergonomics:

Tilt (Forward/Back): 20° - 53°, 90° (Flat) **Additional Hardware:**

Kensington Lock Slot:

Mount:

VESA Compatible: 100 x 100 mm

Weight (metric):

Gross (kg): 7.1 Net Without Stand (kg): 5.5

Weight (imperial):

Net (lbs): 12.2 Gross (lbs): 15.6

Dimensions (metric) (WxHxD):

Packaging (mm): 643 x 435 x 140 Physical (mm): 573 x 353 x 47

Dimensions (imperial) (WxHxD):

Packaging (in.): 25.3 x 17.1 x 5.5 Physical (in.): 22.6 x 13.9 x 1.9

General:

 ${\it Regulations: cTUVus, FCC-B w/ICES003, DOE\ Energy\ Star\ 7.0,\ DOE\ EPEAT\ Silver,\ TUV-MX-CoC,\ Mexico\ Energy,\ NRCan}$

PACKAGE CONTENTS: LCD Display, AC/DC Adapter, Power Cable , HDMI Cable , USB3.0 Upstream Cable , Audio Cable , Quick Start Guide, ViewSonic Wizard CD-ROM

Warranty: Three-year limited warranty on parts, labor and backlight

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907846911

Accessories:

CB-00008948, CB-00009950, CB-00010555, CB-00010684, CB-00010958, LCD-CABLE-001, LCD-WMK-001, TD-EE-24-03, TD-EEEW-24-01, TD-EEEW-24-02, TD-EW-24-01, TD-EW-24-02, TD-EW-24-03, VSPF2360, cb-00011486

Awards:



Copyright © ViewSonic Corporation 2000-2019. All rights reserved. (06/27/2019 03:00 AM PST)