



Main

| | |
|------------------------------|--|
| Range of product | TeSys F TeSys D control relay TeSys D |
| Range | TeSys |
| Device short name | LADN |
| Product or component type | Auxiliary contact block |
| Range compatibility | TeSys D CR1F contactor |
| Auxiliary contacts operation | Instantaneous |
| Pole contact composition | 3 NO + 1 NC |
| Connections - terminals | Screw clamp terminals 1 cable 1...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 1...2.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 1...2.5 mm ² - cable stiffness: solid - with cable end Screw clamp terminals 1 cable 1...2.5 mm ² - cable stiffness: solid - without cable end Screw clamp terminals 2 cable 1...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 1...2.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 1...2.5 mm ² - cable stiffness: solid - with cable end Screw clamp terminals 2 cable 1...2.5 mm ² - cable stiffness: solid - without cable end |

Complementary



| | |
|---|--|
| Mounting location | Front |
| [Ui] rated insulation voltage | 690 V - conforming to IEC 60947-5-1 600 V - certifications CSA 600 V - certifications UL |
| [Ue] rated operational voltage | 690 V AC 25...400 Hz |
| [Ith] conventional free air thermal current | 10 A at ≤ 60 °C |
| Irms rated making capacity | 140 A at ≤ 690 V AC conforming to IEC 60947-5-1 250 A at ≤ 690 V DC conforming to IEC 60947-5-1 |
| Permissible short-time rating | 100 A at 60 °C 1 s 120 A at 60 °C 500 ms 140 A at 60 °C 100 ms |
| Protection type | GG fuse ≤ 10 A rating according to operational current for Ue ≤ 690 V |

| | |
|---------------------------|---|
| Associated fuse rating | 10 A gG IEC 60947-5-1 |
| Mechanical durability | 30 Mcycles |
| Minimum switching current | 5 mA |
| Minimum switching voltage | 17 V |
| Non-overlap time | 1.5 ms on de-energisation (no overlap between NC and NO contact) 1.5 ms on energisation (no overlap between NC and NO contact) |
| Overlap time | 1.5 ms |
| Insulation resistance | > 10 MOhm |
| Product weight | 0.05 kg |

Environment

| | |
|---------------------------------------|---|
| Environmental characteristic | Normal environment |
| Standards | VDE 0660 BS 4794 NF C 63-140 IEC 60947-5-1 EN 60947-5-1 |
| Product certifications | CSA UL |
| IP degree of protection | IP2x conforming to VDE 0106 |
| Protective treatment | TH conforming to IEC 60068 |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -60...80 °C |
| Operating altitude | 3000 m without derating in temperature |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0629 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available  Product Environmental Profile |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|