

# CP-6921-C-K9 Datasheet

[Get a Quote](#)

## Overview

Cisco Unified IP Phone 6921 is an innovative endpoint that delivers affordable, business-grade voice communications and support for video communications services to customers worldwide.

The Cisco Unified IP Phone 6921 supports two lines and offers a full-duplex speakerphone for a more productive, more flexible, and easier-to-use endpoint experience. The Cisco Unified IP Phone 6921 supports multi-call per-line appearance, offering end user the opportunity to handle multiple calls per directory number (DN). Fixed keys for hold, transfer, and conference; tri-color LED line and feature keys also make the phone simpler and easier to use.

The Cisco Unified IP Phone 6921 offers greater personalization, with the choice of two colors and two handset style options. Right-to-left language presentation is also supported on the displays, addressing the language localization needs of global customers.

The Cisco Unified IP Phone 6921 is also more energy-efficient and eco-friendly, in support of customer green initiatives. A Deep-Sleep option provides energy savings. With this option, the Cisco Unified IP Phone 6921 consumes up to 50 percent less power in off-hours versus when the phone is idle during normal business hours. In addition, reground and recyclable plastics deliver a more earth-responsible solution.

## Specification

Specification	Description
Firmware upgrades	You can download firmware changes from Cisco.com.
Software upgrades	Software upgrades are supported with a Trivial File Transfer Protocol (TFTP) server.
Dimensions (H x W x D)	Cisco Unified IP Phone 6921: 164 x 188 x 205 mm (6.4 x 7.4 x 8.1 in.).
Weight	Cisco Unified IP Phone 6921: Standard: 1031g (36 oz); Slimline: 940g (33 oz).
Phone casing composition	Polycarbonate acrylonitrile butadiene styrene (ABS) plastic.

### Power Requirements

Power Requirement	Description
IEEE 802.3af PoE	The phones can receive power from IEEE 802.3af-compliant blades.

### AC Region and Country-Specific Power Cords

Part Number	Country
CP-PWR-CORD-AP=	Asia Pacific
CP-PWR-CORD-AR=	Argentina
CP-PWR-CORD-AU=	Australia
CP-PWR-CORD-CE=	European Community
CP-PWR-CORD-CN=	China
CP-PWR-CORD-JP=	Japan
CP-PWR-CORD-NA=	North America
CP-PWR-CORD-SW=	Switzerland
CP-PWR-CORD-UK=	United Kingdom

### Temperature Ratings

Temperature Variable	Description
Operating temperature	32 to 104°F (0 to 40°C)

Relative humidity	10 to 95% (noncondensing)
Storage temperature	14 to 140°F (-10 to 60°C)

## Want to Buy

---

[Order Now](#)[Get a Quote](#)

## Why Router-switch.com

---

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



16,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

## Contact Us

---

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: [sales@router-switch.com](mailto:sales@router-switch.com)