

ViewSonic® LED DISPLAY **VA2407h**

Key Features

- HDMI and VGA inputs
- ViewMode technology
- Flicker-Free and Blue Light Filter
- Eco-mode
- VESA mountable



Product Description

The ViewSonic VA2407h is a practical 24" (23.6" viewable) Full HD LED monitor designed with matte and hairline surface bezel design. Featuring an HDMI input, it is perfect for daily office work and home entertainment. It also carries eye-care technology, including Flicker-Free and Blue Light Filter, to help eliminate eye strain from viewing for extended periods of time. Furthermore, Viewsonic's exclusive ViewMode™ provides intuitive presets to deliver optimized screen performance in different applications, with an energy-saving Eco-mode that enables users to do documental processing or internet surfing while saving.

Visit Us — www.viewsonic.com

LCD PANEL

Type:	24"W (23.6" Viewable) TN LCD monitor
Display Area:	521.28mm (H) x 293.22mm (V)
Resolution:	Full HD 1920 x 1080
Brightness:	250 cd/m2 (Typ)
Contrast Ratio:	1000:1 (Typ)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angles:	170 degrees / 160 degrees (Typ)
Response Time:	Tr+Tf: 3ms (GtG)
Backlight:	1 WLED light bar
Backlight Life:	20,000 Hrs (Min)
Colours:	16.7M colors (6-bit+Hi-FRC)
Colour Gamut:	72% of NTSC (Typ)
Panel Surface:	Anti-Glare type, Hard-coating (3H), Haze 25%

INPUT SIGNAL

Frequency:	Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz
Sync:	Separate Sync

COMPATIBILITY

PC:	PC Compatibles (VGA up to 1920 x 1080 Non- Interlaced)
Mac®:	Power Mac (up to 1920 x 1080)

CONNECTOR

Digital:	HDMI x 1 (v1.4 compatible)
Analog:	DB -15 x 1
Audio Out:	Earphone out x 1 (3.5mm plug)
Audio In:	N/A

SPEAKERS

N/A

USB

N/A

WEBCAM

N/A

POWER

Power:	Internal Power Board , 3- pin plug (CEE22) x1
Voltage:	AC 100-240V (Universal); 50/60 Hz
Consumption:	20.5W
Optimize:	17.5W
Conserve:	14.8W

ERGONOMICS

Tilt: 21~ -6 degrees

SPECIAL FEATURES

Eye-care, ViewMode

WALL MOUNT

VESA®:	75mm x 75mm
--------	-------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	551.73mm (W) x 403.79mm (H) x 196.95mm (D)
Physical without stand (mm):	551.73mm (W) x 336.76mm (H) x 47.45mm (D)
Packaging (mm):	611mm (W) x 450mm (H) x 120mm (D)

WEIGHT

Net with stand (kg):	3.1kg
Net without stand (kg):	2.9kg
Gross (kg):	4.2kg

REGULATIONS

CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO
--

WARRANTY

*Warranty offered may differ from market to market
--

PACKAGE CONTENTS

LCD Display Power Cable D-Sub Video Cable Quick Start Guide
*Actual content may differ from market to market