

# ViewSonic® LED DISPLAY VA2419-sh

## Key Features

- SuperClear® IPS technology
- Frameless bezel
- HDMI and VGA inputs
- ViewMode technology
- Flicker-Free and Blue Light Filter



## Product Description

The ViewSonic® VA2419-sh is a 24" (23.8" viewable) Full HD LED monitor with SuperClear® IPS Panel technology, offering clearly sharp color representation and outstanding screen performance at wide viewing angles. It is modernized with a minimalistic, borderless design which provides exceptional viewing experience for home entertainment or office work. It also carries eye-care technology, including Flicker-Free and Blue Light Filter, helping to eliminate eye strain from viewing for extended periods of time. Furthermore, Viewsonic's exclusive ViewMode™ provides intuitive presets to deliver optimized screen performance in different applications, with an energy-saving Eco-mode that enables users to do documental processing or internet surfing while saving. Built in with HDMI and VGA inputs, promising more flexible and reliable connectivity. With a 3-year warranty, Energy Star and EPEAT Silver certification, the VA2419-sh definitely is a great long-term investment for home and office users.

Visit Us  [www.viewsonic.com](http://www.viewsonic.com)

**LCD PANEL**

Size:	24" (16:9) IPS Technology
Display Area:	23.8" (527.04x296.46mm)
Optimum Resolution:	1920x1080 (Full HD)
Brightness:	250 cd/m <sup>2</sup>
Contrast Ratio:	1,000 :1
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angle:	178° (H) / 178° (V)
Response Time:	GTG(Avg ): 5ms
Backlight Life:	30000 Hrs (Min.)
Color Support:	16.7 M
Panel Surface:	Anti-Glare type, Hard-coating (3H), Haze 25%

**INPUT SIGNAL**

Analog:	VGA
Digital:	HDMI
Sync:	Separate Sync
Frequency:	24 ~82 kHz / 50 ~75 Hz

**COMPATIBILITY**

PC:	1920x1080
Mac:	1920x1080

**CONNECTOR**

Analog:	VGA x1
Digital:	HDMI x1
Audio Out:	3.5mm jack x1
Power:	Internal Power Board

**POWER**

Voltage:	AC 100-240V (Universal); 50/60 Hz
Consumption:	26 W ; Optimize:22 W (Typ.) ; Conserve: 19 W (Typ.)
Save mode:	0.3 W

**ERGONOMICS**

Tilt:	22° ~ -7°
-------	-----------

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS**

Physical with stand:	547.8 (W) x 403.76 (H) x 215 (D) mm
----------------------	-------------------------------------

**WEIGHT**

Net with stand:	3.8Kg
Gross:	4.8Kg

**REGULATIONS**

CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, EEL, WEEE, BSMI, PSB, RCM, MEPS, CCC, CEL Level 1, China RoHS, TCO7.0

**VESA WALL MOUNT**

100x100 mm
------------

**PACKAGE CONTENTS**

LCD Display/ Power Cable (1.5m)/ VGA Cable (1.5m)/ Quick Start Guide