

# ViewSonic® LED DISPLAY **VA2719-sh**

## Key Features

- SuperClear® IPS technology
- Frameless bezel
- HDMI and VGA inputs
- ViewMode technology
- Flicker-Free and Blue Light Filter



## Product Description

The ViewSonic® VA2719-sh is a 27" (27" viewable) Full HD LED monitor with SuperClear® IPS-Type technology, offering clearly sharp color representation and outstanding screen performance at wide viewing angles. It is modernized with a minimalistic, borderless design which provides exceptional viewing experience for home entertainment or office work. It also carries eye-care technology, including Flicker-Free and Blue Light Filter, helping to eliminate eye strain from viewing for extended periods of time. Furthermore, Viewsonic's exclusive ViewMode™ provides intuitive presets to deliver optimized screen performance in different applications, with an energy-saving Eco-mode that enables users to do documental processing or internet surfing while saving. Integrated HDMI, and VGA inputs options, the VA2719-sh provides a complete multimedia package for home entertainment. With a 3-year warranty, Energy Star and EPEAT Silver certification, the VA2719-sh definitely is a great long-term investment for home and office users.

**Visit Us** ■ [www.viewsonic.com](http://www.viewsonic.com)

**LCD PANEL**

Size:	27" (16:9)
Panel Technology:	IPS Technology
Display Area:	27" (597.888x336.312mm)
Optimum Resolution:	1920x1080 (Full HD)
Brightness:	300 cd/m <sup>2</sup> (Typ), 250 cd/m <sup>2</sup> (Min)
Contrast Ratio:	1,000:1 (Typ), 700:1 (Min)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angle:	178° (H) / 178° (V)
Response Time:	5ms(GTGavg) in OD
Panel Surface:	Anti-Glare type, Hard- coating (3H)
Light Source:	30000 Hrs (Min.)
Color Support:	16.7 M(6 bits +2 bits scalar FRC)

**INPUT**

Analog:	VGA
Digital:	HDMI
Sync:	Separate Sync
Frequency:	24 ~82 kHz / 50 ~75 Hz

**COMPATIBILITY**

PC:	1920x1080
Mac:	1920x1080

**CONNECTOR**

Analog:	VGA x1
Digital:	HDMI x1
Audio Out:	3.5mm jack x1
Power:	Internal Power Board

**POWER**

Voltage:	AC 100-240V (Universal); 50/60 Hz
Consumption:	28W ; Optimize: 23W ; Conserve: 18W

**ERGONOMICS**

Tilt:	22° ~ -5°
-------	-----------

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS**

Physical with stand:	620.2 x 443.8 x 250 mm
----------------------	------------------------

**WEIGHT**

Net with stand:	5.6Kg
-----------------	-------

**REGULATIONS**

CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, EEL, WEEE, EAC, BSMI, RCM, MEPS, VCCI, PSE, CCC, China RoHS, CEL Level 1

**WALL MOUNT**

VESA:	100x100 mm
-------	------------

**PACKAGE CONTENTS**

LCD Display / Power Cable / VGA Cable / Quick Start Guide
-----------------------------------------------------------