

sanwa

TA55

Analog Multitesters / Automotive

MADE IN JAPAN
日本製造

Basic Features

- High level panel visibility
- Continuity check buzzer
- Tilt-stand
- Measureable up to DC30A / DC300A with optional clamp probe
- Automotive battery check (12V)

Bandwidth : 40~5kHz

Optional Accessories

Clamp probe : CL33DC
Carrying case : C-SPH, C-SP
Adapter : CL-14, CL-15a, CL-DG3a, TL-9IC
Test lead : TL-91M, TLF-120

Specifications



TA55	Measuring range	Accuracy
DCV	0.3/3/16/30/60V (20k Ω /V)	$\pm 3\%$ of full scale
ACV	30/120/300V (9k Ω /V)	$\pm 4\%$ of full scale
DCA	0.5/3/30A	$\pm 5\%$ of full scale
Resistance	2k/20k/200k/2M Ω	$\pm 3\%$ of arc
Continuity	Buzzer sounds at less than approx. 70 Ω . Open voltage : 3V	
Bandwidth	40~5kHz	
Battery	R6P \times 2	
Fuse	ϕ 6.3 \times 30mm (250V/3A)	
Size / Mass	H142 \times W97 \times D38mm/approx. 300g	
Standard accessories included	Test lead (TL-91), Instruction manual	

The value in () at DCV and ACV is input resistance.

Copyright © 2012 Sanwa Electric Instrument Co., Ltd. All Rights Reserved.