Product data sheet Characteristics

33682

adjustable time delay relay for voltage release MN - 200/250 V AC/DC



-1	١,	п	9		r
-1	v	ı	а	н	ш

Device short name	MN delay unit	<u>.</u>
Product or component type	Time delay auxiliary	
Device application	Control	<u>ت</u> م
Range compatibility	Masterpact - Masterpact NW Masterpact - Masterpact NT Compact - Compact NSX Compact - Compact NS630b1600 Compact - Compact NS1600b3200 PowerPact - PowerPact Multistandard	see products for speci
Offer type	C4 C5	h Jo Alliyo
Voltage release type	Instantaneous	
[Uc] control circuit voltage	200250 V AC 50/60 Hz 200250 V DC	ein in ein ein ein ein ein ein ein ein e

Complementary

Impulse duration	200 ms	- 0
Time delay range	0.53 s	
Threshold tripping voltage	0.350.7 Un - during open time	
	0.85 Un - during close time	
Supply holding power	4.5 VA	.9
Supply inrush power	200 VA	
Response time	0.5 s	<u> </u>
	0.9 s	,
	1.5 s	4
	3 s	c S
Accessory / separate part category	Spare part Compact NS630b1600	
	Spare part Compact NS1600b3200	-

Contractual warranty

_	Warranty period	18 months