



### Main

Range of product	EZC250 EZCV250
Range	EasyPact
Device short name	AL AX
Product or component type	Switch
Device application	Signalling Alarm
Signal contacts composition	2 NO/NC

### Complementary

Auxiliary contacts type	Standard
[I <sub>th</sub> ] conventional free air thermal current	5 A
[I <sub>e</sub> ] rated operational current	DC-12 : 2.5 A DC 48 V AC-15 : 2 A AC 50/60 Hz 250 V DC-12 : 0.2 A DC 250 V DC-14 : 0.2 A DC 250 V AC-12 : 3 A AC 50/60 Hz 250 V AC-15 : 5 A AC 50/60 Hz 48 V DC-14 : 1 A DC 48 V DC-12 : 0.4 A DC 125 V AC-12 : 5 A AC 50/60 Hz 24 V DC-12 : 4 A DC 24 V AC-12 : 5 A AC 50/60 Hz 48 V AC-15 : 5 A AC 50/60 Hz 24 V AC-12 : 5 A AC 50/60 Hz 125 V DC-14 : 0.4 A DC 125 V DC-14 : 3 A DC 24 V AC-15 : 3 A AC 50/60 Hz 125 V
Minimum load	10 mA at 24 V
Auxiliary connection terminal	Lead wire

### Contractual warranty

Warranty period	18 months
-----------------	-----------