



### Main

Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600 Compact Compact NSX Compact Compact NG Compact Compact NR Easypact EasyPact CVS Compact Compact INS Compact Compact INSE Compact Compact INSJ Compact Compact INV
Offer type	C4 C5
Signal contacts composition	1 NO/NC

### Complementary

Auxiliary contacts type	Low level
Auxiliary contacts operation	Early-break Early-make
Mounting mode	Clip-on
[I <sub>th</sub> ] conventional free air thermal current	5 A
[I <sub>e</sub> ] rated operational current	Utilisation category DC-12 : 0.3 A network: DC at 250 V Utilisation category DC-12 : 0.6 A network: DC at 110 V Utilisation category DC-12 : 2.5 A network: DC at 48 V Utilisation category DC-14 : 0.03 A network: DC at 250 V Utilisation category DC-14 : 0.05 A network: DC at 110 V Utilisation category DC-14 : 0.2 A network: DC at 48 V Utilisation category DC-14 : 1 A network: DC at 24 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 250 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 48 V Utilisation category AC-12 : 5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 480 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Utilisation category AC-15 : 1.5 A network: AC 50/60 Hz at 380/440 V  
Utilisation category AC-15 : 2 A network: AC 50/60 Hz at 220/240 V  
Utilisation category AC-15 : 2.5 A network: AC 50/60 Hz at 110 V  
Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 24 V  
Utilisation category AC-15 : 3 A network: AC 50/60 Hz at 48 V  
Utilisation category DC-12 : 5 A network: DC at 24 V

Minimum load	1 mA at 4 V DC
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0701 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
Product environmental profile	Available <a href="#">Product Environmental Profile</a>
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------