

TES-1350R Sound Level Meter (RS232)



Standard applied IEC 651 Type2 **Range** LO (Low) - Weighting: 35- 00dB

A HI (High) - Weighting: 65-130dB

C LO (Low) - Weighting: 35- 100dB

C HI (High) - Weighting: 65-130dB **Resolution** 0.1dB **Frequency**

Range 31.5Hz to 8KHz **Accuracy** ± 2 dB **Dynamic Range** 65dB **Frequency**

Weighting A, C **Time Weighting** Slow & Fast **Maximum Hold** Decay <

1dB/3min **Microphone** Electret condenser microphone **Calibration** Electrical calibration by using the internal oscillator

(1KHz sine Wave at 94dB) **Auxiliary Output** AC conditioned, 0.65Vrms corresponding to

each range step, impedance: 600 Ω

DC conditioned, 10mV/dB (nominally) **Operating Condition** 0°C to 40 °C <

80% R. H. **Storage Condition**-10°C to 60 °C < 70% R.H. **Display**3 1/2

digitals **Power Supply**one 9V

battery **Size**240mm(L)x68mm(W)x25mm(H) **Weight**215g **Accessories**Instruction Manual, 9V Battery, Carrying Case,

Screwdriver, Windscreen., Software , Wind shield, RS-232 connecting